

Apacer

The Most **Reliable**
Storage For Industries

SV25C-M242



SV25C-M242

Overview

Apacer's SV25C-M242 is a well-balanced solid-state disk (SSD) drive with standard form factor and great performance. Designed in SATA 6.0 Gb/s interface, the SSD is able to deliver exceptional read/write speed, making it the ideal companion for heavy-loading industrial or server operations.



SV25C-M242 utilizes 3D NAND for higher capacity up to 480GB and provides more power efficiency than 2D NAND. Regarding reliability, SV25C-M242 is implemented with LDPC (Low Density Parity Check) ECC engine to extend SSD endurance and increase data reliability. In addition, the drive comes with various implementations including powerful hardware ECC engine, power saving modes, Wear Leveling, flash block management, S.M.A.R.T., TRIM, and DataDefender™ .

In terms of security, Advanced Encryption Standard (AES) ensures data security and provides users with a peace of mind. Furthermore, with End-to-End Data Protection, data integrity can be assured at multiple points in the path to enable reliable delivery of data transfers

SV25C-M242

Ensures Highly Efficient System Operation with DBS Cloud Edition

Apacer SV25C cloud series SSDs are equipped with Double-barreled Solution: Cloud Edition. Double-barreled Solution: Cloud Edition is a solution designed to monitor the typical pain points of an IoT edge device network. DBS Cloud Edition automatically collects data related to SSD temperatures, unexpected power outages, remaining lifespan, and operating status, and instantly transmits the data to the back-end management platform. Users can then observe this data as it comes in, thanks to the intuitive dashboard interface.



In the event of an abnormality, the system can also send messages to network administrators through Email, LINE, WeChat, and other communication platforms, so that admins can react to critical events in real-time even if they aren't on location. The alerts can even be color-coded to allow admins to determine the severity of a problem at a glance.

Existing Integrated Remote Device Management Systems

Apacer has also collaborated with Advantech and Allxon to develop the DBS Cloud Edition. It offers customers greater choice in deploying and remote device management system and adds flexibility while retaining seamless integration to significantly reduce customer deployment time and costs.


Feature

- SV25C cloud series
- Adopts advanced LDPC ECC engine with 3D NAND flash memory to improve reliability
- Global Wear Leveling
- Flash bad-block management
- Flash Translation Layer: Page Mapping
- S.M.A.R.T.
- DataDefender™
- Device Sleep
- ATA Secure Erase
- TRIM
- Hyper Cache Technology
- Over-Provisioning
- DataRAID™
- SMART Read Refresh™
- Double-barreled Solution Cloud Edition

Specifications

Model	SV25C-M242
Interface	SATA 3.2 (6Gb/s)
Connector	M.2 B & M key
Form Factor	M.2 2242-D5-B-M
NAND Flash Type	3D TLC
Capacity	30GB~480GB
External DRAM	No
Sustained Read Performance (MB/sec)	Up to 560
Sustained Write Performance (MB/sec)	Up to 560
ECC Engine	Low-Density Parity-Check (LDPC) Code
IOPS (4K Random Write)	73K
Standard Operating Temperature (°C)	0 ~ + 70
Extended Operating Temperature (°C)	-40 ~ + 85
Storage Temperature (°C)	-40 ~ + 100
Thermal Sensor	Yes
Shock	Operation: 50G, 11ms Non-operation:1500G, 0.5ms (compliant with MIL-STD-883K)
Vibration	Operation:7.69(Grms), 20~2000(Hz)/random (compliant with MIL-STD-810G) Non-operation:4.02(Grms), 15~2000(Hz)/random (compliant with MIL-STD-810G)
Operating Voltage	3.3V ± 5% (3.135-3.465V)
Power Consumption	Active mode: 405 mA / Idle mode: 70 mA
Dimension (L x W x H)	42.00 x 22.00 x 3.80 (mm)
MTBF (hours)	>3,000,000

Mechanical Specification



Unit: mm

For more information,
contact your Apacer representative

Global Presence

Taiwan (Headquarters)
Apacer Technology Inc.
Tel: +886-2-2267-8000
Fax: +886-2-2267-2261

Europe
Apacer Technology B.V.
Tel: +31-40-267-0000
Fax: +31-40-290-0686

U.S.A.
Apacer Memory America, Inc.
Tel: +1-408-518-8699
Fax: 1-510-249-9551

China
Apacer Electronic(Shanghai)
Co., Ltd.
Tel: +86-21-6228-9939

Japan
Apacer Technology Corp.
Tel: +81-3-5419-2668
Fax: +81-3-5419-0018

India
Apacer Technologies Pvt. Ltd.
Tel: +91-80-41529061~3
Fax: +91-80-41700215